


COMPRESSION SEAL


CONCRETE OPENING


- 1 USE 1/2" FOR ALL SEALS.
- 2 USE 1/2" FOR ALL SEALS.
- 3 COMPUTE "A CONSTR." PER EQUATION (12) @ 40°F, 64°F, AND 80°F.
- TO BE CHECKED BY THE DESIGNER. SHALL BE LARGE ENOUGH TO PREVENT CLOSURE UNDER THERMAL MOVEMENTS.
- 5 SEE BDM SECTION 9.1.3A AND DESIGN EXAMPLE FOR COMPRESSION SEAL DESIGN AND SEE "COMPRESSION SEAL TABLE" ON THIS SHEET.




COMPRESSION SEAL

ARMORED OPENING. USE IN BRIDGE WIDENINGS WITH EXISTING ARMORED JOINTS









SEAL CUTTING DETAIL


COMPRESSION SEAL TABLE

20 21	201111	WATSON BOWMAN ACME					
D.S. BR	COWN						
SEAL	WIDTH	SEAL	WIDTH				
CV-2000	2"	WA-200	2"				
CV-2502	21/2"	WA-250	2½"				
CV-3000	3"	WA-300	3"				
CV-3500	3½"	WA-350	3½"				
CV-4000	4"	WA-400	4"				

TESTING SHALL BE PER AASHTO M-220 PRIOR TO USE.

NOTE:

COMPRESSION SEALS GREATER THAN FOUR INCHES WIDE SHOULD NOT BE USED



`									
Bridge Design Engr.	EAL DE	T.man							
Supervisor					REGION NO.	STATE	FED, AID PROJ, NO,	SHEET NO.	TOTAL SHEETS
Designed By									
Checked By					10	WASH.			
Detailed By					TOP	II IMPED			
Bridge Projects Engr.					JOB NUMBER				
Prelim. Plan By									
Architect/Specialist	DATE	REVISION	BY	APP'D					

BRIDGE AND STRUCTURES OFFICE



EXPANSION JOINTS

SHEET

EXPANSION JOINT DETAILS

COMPRESSION SEAL

SHEET

OF

-18-1 sr_

Tue Mav 08 06:58:08:1201211/97